



## Magnetic Signs

### Magnetic Sign Care Guide:

Magnetic signs do not adhere to non-ferrous materials such as aluminium, fibre-glass, plastics or vehicle body work that has been repaired with body filler or excessive amounts of paint. They should not be applied over body mouldings or chrome strips.

**Surface Preparation:** Clean off the surface thoroughly with a mild detergent; wipe the surface dry with a clean cloth. We recommend the area is then treated with a good quality silicone polish.

**Application:** The magnetic sign should be clean, dry and at room temperature. Hold the sign in position and allow one edge to make contact with the surface, gently smooth the sign down ensuring good contact without kinks or bubbles. If necessary repeat this procedure until the desired position is attained. (Do not attempt to reposition without removing the sign completely).

**Cleaning and Maintenance:** Magnetic signs should be removed once a week and cleaned with mild detergent, the surface prepared and the sign re-applied as described above.

**Storage:** Magnetic sign can be kept loosely rolled for short periods but ideally they should be stored flat, clean and dry, and sandwiched between two pieces of card.

Any questions please contact us at:

[support@michaelmurraysigns.ltd.uk](mailto:support@michaelmurraysigns.ltd.uk)

[www.michaelmurraysigns.ltd.uk](http://www.michaelmurraysigns.ltd.uk)